



FLOOR AREA: 3,016 SQM
LOADING:
FLOOR: 7.5 kpa
 THE SLAB CAN CARRY A SINGLE AXLE LOAD OF SIX (6) TONNES IN LIMITED REPETITION
ROOF: MAXIMUM WEIGHT HUNG FROM STEEL FRATER & PURLINS TO BE 100KG DEAD LOAD, TIED BACK TO THREE POINTS OF CONTACT.
SUPPLY CAPACITY: MDB - H1 - 400A

NOTE: BUILDING SPECIFICATIONS FOR B-01 (FORMALLY N-1) AS SUPPLIED BY DARYL JACKSON ARCHITECTS 14-07-2006

SERVICES

DB OR COMMS. RACK		VENUE EXIT	
OUTLET 240 10 AMP TYP.		DEFIBRILLATOR	
OUTLET 3 PHASE			
FIRE HOSE REEL			
EXTINGUISHER			
COLD WATER POINT			
SEWER OUTLET			

AREAS TO BE KEPT CLEAR

NO BUILD ZONE

Disclaimer
 This drawing is a representation only. Royal Melbourne make no representations about the accuracy of the information contained herein, not for construction or event build purposes. All measurements & equipment need to be checked on site. Do not scale. If in doubt, consult the Duty engineer or Operations Manager.

Copyright
 All rights reserved. This work is copyright & cannot be reproduced or copied in any form or by any means (graphic, electronic or mechanical, including photocopying) without the written permission of the content provider. Any licence, expressed or implied, to use this document for any purpose whatsoever is restricted to the terms of the agreement or implied agreement between the content provider and the instructing party.

